	_	L	
(19)Japanese	Patent	Office	(JP)

(12) Publication of Utility Model Application (U)

(11) Publication Number

HEI 5-43622

	(43) Publication Date: June 11, 1993						
(51) Int.Cl.5 Identifica	tion Symbol	Inte	ernal File No		FI	Techn	ology Indication Part
H 03 K 17/687							
17/693		Α	8221-5J				
			8221-5J	Н	03 K	17/687	G
					Reques	st for Examina	tion: Not Requested
					_	r of Claims:2	•
(21) Application No.:	HEI 3-9161	13					
(22) Filing Date:	November 8	3, 1	991				
(71) Applicant:	000003078	;					
	TOSHIBA CORPORATION						
	72, Horikawacho, Saiwai-ku, Kawasaki-shi, Kanagawa JAPAN						

(72) Creator: Osamu SASAKI

c/o Hino Factory, TOSHIBA CORPORATION

1-1, Asahigaoka 3-chome, Hino-shi, Tokyo Japan

(72) Creator: Kenji FUKUNABE

c/o Hino Factory, TOSHIBA CORPORATION

1-1, Asahigaoka 3-chome, Hino-shi, Tokyo Japan

(74) Agent: Patent Attorney: Takehiko SUZUE

(54) Title: High-Frequency Switching Circuit

## **IDS 03P426US IDS**

Japanese Utility Model Publication No. 5-43622

## (51) [Abstract]

[Objective] A high-frequency switching circuit is configured to operate only at a positive potential without a need for a circuit for generating a negative potential. Thereby, a small-sized device, improvement of S/N, and low power consumption are achieved while inhibiting heat generation or generation of a noise.

[Configuration] A bias voltage at a positive potential (+4V) is applied to a source electrode and a drain electrode of a switching device 1 comprising a MES type FET on a fixed basis. The positive potential (+4V) which is equipotential to the bias voltage at the above positive potential or a ground potential is selectively applied to a gate electrode as a control voltage to cause the switching device 1 to be turned ON and OFF.

